

KOP-COAT, INC  
 MARINE GROUP EAST  
 36 PINE STREET  
 ROCKAWAY  
 NJ 07866

EMERGENCIES  
 HEALTH/SPILLS.....: 800-548-0489  
 CHEMTREC ASSISTANCE: 800-424-9300  
 CHEMTREC OUTSIDE US: 703-527-3887  
 CANUTEC.....: 613-996-6666

KOP-COAT, INC  
 PRODUCT INFORMATION: 800-221-4466  
 OUTSIDE USA.....: 973-625-3100

-----  
 1 PRODUCT IDENTIFICATION  
 -----

PRODUCT NAME: 1318 Unepoxy Plus Green  
 PRODUCT USE.: Antifouling bottom paint  
 APPEARANCE..: Green liquid with hydrocarbon odor  
 CAS NUMBER..: Mixture  
 SYNONYMS....: None

REVISION...: 2  
 DATE.....: 10/12/00  
 MSDS NUMBER: 1131800

-----  
 2 HAZARDOUS INGREDIENTS  
 -----

<u>HAZARDOUS COMPONENT</u>	<u>REG AGENCY</u>	<u>PPM</u>	<u>NOTES</u>	<u>MG/M3</u>	<u>NOTES</u>
Cuprous oxide CAS NUMBER:1317-39-1 PERCENT BY WGT: 50 TO 55	ACGIH-TLV OSHA-TWA			1.0 1.0	
Xylene CAS NUMBER:1330-20-7 PERCENT BY WGT: 1 TO 5	ACGIH STEL ACGIH-TWA NIOSH NIOSH STEL OSHA STEL OSHA TWA	150 100 100 150 150 100		651 434 435 655 655 435	
Titanium dioxide CAS NUMBER:13463-67-7 PERCENT BY WGT: 5 TO 10	ACGIH-TWA NIOSH OSHA TWA	- - -	(+)	10 - 10	(+) 1
Petroleum distillates CAS NUMBER:64742-94-5 PERCENT BY WGT: 15 TO 20	OSHA PEL	100		-	
Petroleum distillates CAS NUMBER:64742-95-6 PERCENT BY WGT: 1 TO 5	OSHA-PEL	100		-	
1,2,4 Trimethylbenzene			(None established.)		

-----  
 2 HAZARDOUS INGREDIENTS  
 -----

HAZARDOUS COMPONENT	REG AGENCY	PPM	NOTES	MG/M3	NOTES
---------------------	------------	-----	-------	-------	-------

CAS NUMBER:95-63-6  
 PERCENT BY WGT: 1 TO 5

NOTES:

- 1) Total dust
- (+)) NIOSH Occupational Carcinogen

-----  
 3 HAZARDS IDENTIFICATION  
 -----

EYE: Direct contact with liquid or vapor may cause irritation.

SKIN: Prolonged or repeated contact with the skin can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). May be absorbed through the skin resulting in systemic effects.

INHALATION: Avoid breathing vapors or mists. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches). Prolonged or repeated inhalation and ingestion may cause delayed injury involving the kidneys and the blood. Prolonged or repeated inhalation of high concentrations of metal fumes may cause metal fume fever characterized by headache, dizziness, metallic taste in mouth and general flu-like symptoms.

INGESTION: Irritating to the nose, throat and respiratory tract. May cause vomiting. Aspiration of this product into the lung may cause chemical pneumonitis which can be fatal.

Individuals with pre-existing disease in or a history of ailments involving the skin, eye, respiratory tract, liver, kidney, central nervous system are at a greater than normal risk of developing adverse effects when exposed to this material.

-----  
 4 FIRST AID MEASURES  
 -----

EYE CONTACT: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wash thoroughly with soap and water. If redness, itching, burning or other symptoms develop or persist, get medical attention. Wash contaminated clothing before reuse.

INHALATION: If you experience difficulty in breathing, leave the area to obtain fresh air. If breathing has stopped have a trained person administer artificial respiration preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

-----  
4 FIRST AID MEASURES  
-----

INGESTION: If swallowed do NOT induce vomiting. Give victim a glass of water or milk. Get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

NOTE TO PHYSICIAN: There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

-----  
5 FIRE FIGHTING MEASURES  
-----

FLASH POINT: 74 F/23 C

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, water spray or foam.

FIRE FIGHTING PROCEDURES: As in any fire, wear complete fire service protective equipment, including full-face MSHA/NIOSH approved or equivalent self-contained breathing apparatus. Use water to cool fire-exposed container/structure/protect personnel.

FIRE AND EXPLOSION HAZARDS: Can release vapors that form explosive mixtures. Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat (fire). Toxic vapors may be given off in a fire.

-----  
6 SPILL AND LEAK PROCEDURES  
-----

Stop spill/leak if no risk involved. Avoid breathing vapors. Eliminate ALL sources of ignition. Ventilate area. Take up carefully to avoid heat and sparks. Use an inert absorbent to complete a clean-up. This material reacts with oxidizing materials. Do not discharge into lakes, streams, ponds or public water systems. This pesticide is toxic to aquatic organisms. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

-----  
7 HANDLING AND STORAGE  
-----

HANDLING: Avoid prolonged or repeated contact with skin or eyes. Avoid prolonged or repeated breathing of vapors, mists or fumes. Spray paint in accordance with OSHA 29 CFR 1910.107. Use with adequate ventilation. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling.

STORAGE: Keep in a closed, labeled container within a cool (well-shaded), dry,

7 HANDLING AND STORAGE

ventilated area. Protect from physical damage. Keep containers closed when material is not in use. Maintain good housekeeping.

OTHER: Keep away from heat and open flame.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Facilities storing or utilizing this product should be equipped with an eyewash facility.

RESPIRATORS: Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved or equivalent) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. A respiratory protection program that meets 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PERSONAL PROTECTIVE EQUIPMENT: Industrial safety glasses at a minimum. As necessary for work area conditions: use side shields, goggles, or faceshield. As required, chemical resistant flexible-type gloves (heavy duty neoprene or equal). Wear industrial-type work clothing and safety footwear. Depending on working conditions, i.e., contact potential, wear resistant protective garments such as head/neck cover, aprons, jackets, pants, coveralls, boots, etc.

9 PHYSICAL AND CHEMICAL PROPERTIES

Weight Per Gallon (lbs): 17.580 % VOL by Weight.: 50-60
Vapor Density.: (air=1)>1 Boiling Point...: Not determined
Vapor Pressure: Not determined Evaporation Rate: (ether=1)<1
pH.....: Not determined Specific Gravity: > 1
Solubility In Water: Negligible Viscosity.....: Not determined
VOC Content.....: 440 g/L

10 STABILITY AND REACTIVITY DATA

STABILITY: None
HAZARDOUS POLYMERIZATION: None
INCOMPATIBILITY: Avoid oxidizing agents, heat, sparks and open flames.
HAZARDOUS DECOMPOSITION PRODUCT(S): Carbon monoxide, carbon dioxide upon

-----  
10 STABILITY AND REACTIVITY DATA  
-----

thermal decomposition.

-----  
11 TOXICOLOGICAL INFORMATION  
-----

Contact Kop-Coat for applicable information.

-----  
12 ECOLOGICAL INFORMATION  
-----

Product has not been tested for ecotoxicity.

-----  
13 DISPOSAL CONSIDERATIONS  
-----

This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state and federal regulations.

-----  
14 TRANSPORTATION INFORMATION  
-----

DEPARTMENT OF TRANSPORTATION REPORTABLE QUANTITIES

REPORTABLE QTY (LBS)	HAZARDOUS SUBSTANCE
100	Xylene
10	Dibutyl Phthalate
100	Naphthalene

DOT PROPER SHIPPING NAME: Consumer commodity  
DOT HAZARD CLASS: ORM-D  
LABEL: None  
DOT IDENTIFICATION NUMBER: None

-----  
15 REGULATORY INFORMATION  
-----

SARA TITLE III SECTION 313 CHEMICALS

Cuprous oxide (as Cu dust and mists)  
Xylene  
1,2,4 Trimethylbenzene

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

-----  
15 REGULATORY INFORMATION  
-----

EPA Registration Number 60061-66.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

-----  
16 OTHER INFORMATION  
-----

NOTE: The petroleum distillate (CAS# 64742-95-6) may contain approximately 7% xylene, 3% cumene and 40% trimethylbenzene.

NOTICE: While the information and recommendations set forth herein are believed to be accurate as of the date hereof, Kop-Coat, Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.

PREPARED BY: L. Briggs Manager Environmental and Regulatory Affairs