

KOP-COAT, INC
 MARINE GROUP EAST
 36 PINE STREET
 ROCKAWAY
 NJ 07866

EMERGENCIES

HEALTH/SPILLS.....: 800-548-0489
 CHEMTREC ASSISTANCE: 800-424-9300
 CHEMTREC OUTSIDE US: 703-527-3887
 CANUTEC.....: 613-996-6666

KOP-COAT, INC

PRODUCT INFORMATION: 800-221-4466
 OUTSIDE USA.....: 973-625-3100

 1 PRODUCT IDENTIFICATION

PRODUCT NAME: 3801 Easyoxy Black
 PRODUCT USE.: Topside coating
 APPEARANCE..: Black liquid with hydrocarbon odor
 CAS NUMBER..: Mixture
 SYNONYMS....: None

REVISION...: 5
 DATE.....: 7/06/04
 MSDS NUMBER: 1380100

 2 HAZARDOUS INGREDIENTS

<u>HAZARDOUS COMPONENT</u>	<u>REG AGENCY</u>	<u>PPM</u>	<u>NOTES</u>	<u>MG/M3</u>	<u>NOTES</u>
Ethyl Benzene	ACGIH STEL	125		543	
CAS NUMBER:100-41-4	ACGIH-TWA	100		434	
PERCENT BY WGT: < 1	NIOSH	100		435	
	NIOSH STEL	125		545	
	OSHA STEL	125		545	
	OSHA TWA	100		435	
Calcium carbonate	ACGIH-TWA	-		10	1
(Limestone)	OSHA TWA	-		15	1
CAS NUMBER:1317-65-3	OSHA-TWA	-		5	2
PERCENT BY WGT: 5 TO 10					
Carbon black	ACGIH-TWA	-		3.5	
CAS NUMBER:1333-86-4	NIOSH	-	(+)	3.5	8 (+)
PERCENT BY WGT: 1 TO 5	OSHA TWA	-		3.5	
Mineral spirits	ACGIH TWA	100		-	
CAS NUMBER:8052-41-3	NIOSH	-		350	
PERCENT BY WGT: 35 TO 40	OSHA TWA	100		-	

NOTES:

1) Total dust

2 HAZARDOUS INGREDIENTS

NOTES:

- 2) Respirable fraction
- 8) 0.1 mg/m³ in presence of polycyclic aromatic hydrocarbons
- (+) NIOSH Occupational Carcinogen

3 HAZARDS IDENTIFICATION

EYE: Direct contact with liquid or vapor causes irritation.

SKIN: Prolonged or repeated contact with the skin can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). May be absorbed through the skin resulting in systemic effects.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches or unconsciousness). Prolonged overexposure to solvents has been reported to cause brain or nervous system damage. Prolonged overexposure to solvent ingredients may cause adverse effects to the liver and kidneys.

INGESTION: Harmful if swallowed. May cause vomiting, diarrhea and depressed respiration. Aspiration of this product into the lungs due to vomiting may cause chemical pneumonitis which can be fatal.

Individuals with pre-existing disease in or a history of ailments involving the skin, eye, respiratory tract, liver, kidney, central nervous system are at a greater than normal risk of developing adverse effects when exposed to this material.

4 FIRST AID MEASURES

EYE CONTACT: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing the eye.

SKIN CONTACT: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash contaminated clothing before reuse.

INHALATION: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth. Call a poison control center or doctor for further treatment advice.

INGESTION: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious

4 FIRST AID MEASURES

person.

NOTE TO PHYSICIAN: There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

5 FIRE FIGHTING MEASURES

FLASH POINT: 106 F/41C

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, water spray or foam.

FIRE FIGHTING PROCEDURES: As in any fire, wear complete fire service protective equipment, including full-face MSHA/NIOSH approved or equivalent self-contained breathing apparatus. Use water to cool fire-exposed container/structure/protect personnel.

FIRE AND EXPLOSION HAZARDS: Can release vapors that form explosive mixtures. Vapors can travel to a source of ignition and flash back. Closed containers may explode when exposed to extreme heat (fire). Toxic vapors may be given off in a fire.

6 SPILL AND LEAK PROCEDURES

Stop spill/leak if no risk involved. Avoid breathing vapors. Eliminate ALL sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate area. Take up carefully to avoid heat and sparks. Use an inert absorbent to complete a clean-up. This material reacts with oxidizing materials. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

7 HANDLING AND STORAGE

HANDLING: Avoid prolonged or repeated breathing of vapors, mists or fumes. Do not get on skin, in eyes or on clothing. Spray paint in accordance with OSHA 29 CFR 1910.107. Use with adequate ventilation. Wash thoroughly after handling

STORAGE: Store in areas/buildings designed to comply with OSHA 1910.106. Keep in a closed, labeled container within a cool (well-shaded), dry, ventilated area. Protect from physical damage. Keep containers closed when material is not in use. Maintain good housekeeping.

OTHER: Keep away from heat and open flame. If post application/use processing of this product generates dust or if spray application is made, " Exposure

7 HANDLING AND STORAGE

Limits " in Section 2 apply. Do not use until manufacturer's precautions have been read/understood. Containers of this material may be hazardous when empty. Since emptied containers retain product residues (vapor, liquid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger containers, should be grounded and/or bonded when material is transferred.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Facilities storing or utilizing this product should be equipped with an eyewash station and shower.

RESPIRATORS: Ensure fresh air entry during application and drying. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, or if air monitoring demonstrates vapor level is above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved or equivalent) during and after application. Respirator selection, use and maintenance should be in accordance with the requirements in 29 CFR 1910.134 and NIOSH 42 CFR 84, whenever workplace conditions warrant a respirator's use.

PERSONAL PROTECTIVE EQUIPMENT: Industrial safety glasses at a minimum. As necessary for work area conditions: use side shields, goggles, or faceshield. As required, chemical resistant flexible-type gloves (heavy duty neoprene or equal). Wear industrial-type work clothing and safety footwear. Depending on working conditions, i.e., contact potential, wear resistant protective garments such as head/neck cover, aprons, jackets, pants, coveralls, boots, etc.

9 PHYSICAL AND CHEMICAL PROPERTIES

Weight Per Gallon (lbs): 8.220 % VOL by Weight.: Not determined
Vapor Density.: (Air=1)>1 Boiling Point...: Not determined
Vapor Pressure: Not determined Evaporation Rate: (ether=1)<1
pH.....: Not determined Specific Gravity: > 1
Solubility In Water: Negligible Viscosity.....: Not determined
VOC Content.....: 375 g/L

10 STABILITY AND REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.

10 STABILITY AND REACTIVITY DATA

INCOMPATIBILITY: Avoid oxidizing agents, heat, sparks and open flames.
HAZARDOUS DECOMPOSITION PRODUCT(S): Carbon monoxide, carbon dioxide, smoke, fumes, and/or unburned hydrocarbons.

11 TOXICOLOGICAL INFORMATION

Product has not been tested.

12 ECOLOGICAL INFORMATION

Product has not been tested for ecotoxicity.

13 DISPOSAL CONSIDERATIONS

This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state and federal regulations.

14 TRANSPORTATION INFORMATION

DEPARTMENT OF TRANSPORTATION REPORTABLE QUANTITIES	
REPORTABLE QTY (LBS)	HAZARDOUS SUBSTANCE
100	Xylene

DOT PROPER SHIPPING NAME: Consumer commodity
DOT HAZARD CLASS: ORM-D
LABEL: None
DOT IDENTIFICATION NUMBER: None
DOT information for domestic ground transportation.

15 REGULATORY INFORMATION

SARA TITLE III SECTION 313 CHEMICALS
Ethyl Benzene

WARNING: THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

15 REGULATORY INFORMATION

No additional information available.

16 OTHER INFORMATION

Ethylbenzene is considered a Group 2B carcinogen (possibly carcinogenic to humans). This category generally includes agents for which there is limited evidence in humans in the absence of sufficient evidence in experimental animals.

IARC Monograph Vol. 65 reports carbon black is widely used in rubber tires, hoses, gaskets and coated fabrics; smaller amounts are used in printing inks, paints and plastics. Although one cohort study on carbon black production workers showed slight excesses of lung cancer, the totality of the epidemiological studies both in the carbon black production industry and in some user industries suggested that there is inadequate evidence for the carcinogenicity in humans of carbon black. Carbon black was thus evaluated as possibly carcinogenic to humans (Group 2B).

NOTICE: This document is generated for the purpose of distributing health, safety and environmental data. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. Kop-Coat makes no warranty with respect thereto and disclaims all liability from reliance thereon.

PREPARED BY: Manager of Health, Safety and Environmental Affairs

----- END OF MSDS -----