# SAFETY DATA SHEET



Revision Date 18-Nov-2015 Version 1

## 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Product code Pettit Marine Paint Trinidad SR Antifouling Paint 1377 Green A1137706

#### **<u>1.2 Relevant identified uses of the substance or mixture and uses advised against</u>**

Recommended Use Restrictions on use Paint Read label instructions and SDS

## 1.3 Details of the supplier of the safety data sheet

Su	pp	olier

Kop-Coat, Inc. / Pettit Marine Paint Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

## 1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA Chemtrec: 1-800-424-9300 USA

## 2. Hazards identification

## 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Oral	Category 4
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

## 2.2 Label elements

#### A1137706 - Pettit Marine Paint Trinidad SR Antifouling Paint 1377 Green

## Signal Word

Danger

## Hazard Statements

Harmful if swallowed May cause an allergic skin reaction May cause cancer May damage fertility or the unborn child Causes damage to organs through prolonged or repeated exposure Flammable liquid and vapor



## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Contaminated work clothing must not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

## **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell Rinse mouth In case of fire: Use CO2, dry chemical, or foam to extinguish

## **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## 2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

## 2.4 Other information Not Applicable

## Unknown Acute Toxicity

< 1% of the mixture consists of ingredient(s) of unknown toxicity

## 3. Composition/Information on Ingredients

## Substance

Not applicable Mixture

Chemical Name	CAS-No	Weight %
Cuprous oxide	1317-39-1	60 - 70
HEAVY AROMATIC NAPHTHA	64742-94-5	5 - 10
Resin acids	Proprietary	5 - 10
Xylene	1330-20-7	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Cupric Oxide	1317-38-0	1 - 5
Copper (as Cu Dust & Mists)	7440-50-8	1 - 5
SILICA (CRYSTALLINE-CRISTOBALITE)	14464-46-1	1 - 5
Ethylbenzene	100-41-4	< 1
N-METHYL-2-PYRROLIDONE	872-50-4	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

#### 4.1 Description of first-aid measures

General advice	For further assistance, contact your local Poison Control Center.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.	
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.	
Inhalation	Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.	
Ingestion	Rinse mouth. Do NOT induce vomiting. Call a physician or poison control center immediately. If a person vomits when lying on his back, place him in the recovery position.	
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.	
4.3 Indication of any immediate me	edical attention and special treatment needed	
Notes to physician	There is no specific antidote for effects from overexposure to this material. Treat symptomatically.	

## 5. Fire-Fighting Measures

## 5.1 Extinguishing media

#### Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

## 5.2 Special hazards arising from the substance or mixture

## Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to

release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Yes.

#### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

#### 6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

#### 6.3 Methods and materials for containment and cleaning up

Methods for Containment	Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.
Hygiene measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.
7.2 Conditions for safe storage, in	cluding any incompatibilities

# Storage ConditionsKeep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot<br/>surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly

labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

Materials to Avoid

No materials to be especially mentioned.

## 8. Exposure controls/personal protection

#### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Cuprous oxide 1317-39-1	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-				
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Cupric Oxide 1317-38-0	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	-				
Copper (as Cu Dust & Mists) 7440-50-8	TWA: 1 mg/m <sup>3</sup> Cu dust and mist	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist	TWA: 1 mg/m³ TWA: 0.2 mg/m³	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>
SILICA (CRYSTALLINE-CRIS TOBALITE) 14464-46-1	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	: (1/2)(30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA total dust : (1/2)(250)/(%SiO2 + 5) mppcf TWA respirable fraction : (1/2)(10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA respirable fraction	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.05 mg/m³	TWA: 0.05 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm
N-METHYL-2-PYRRO LIDONE 872-50-4	-	-				TWA: 400 mg/m <sup>3</sup>

## 8.2 Appropriate engineering controls

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

## 8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles. Face-shield.
Skin and body protection	Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use. Long sleeved clothing. Protective shoes or boots.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
Hygiene measures	See section 7 for more information

## 9. Physical and chemical properties

9.1 Information on basic physical a Physical state Appearance Color Odor Odor Threshold	Ind chemical properties Liquid No information available Green Hydrocarbon-like No information available	
<u>Property</u> pH Melting/freezing point Boiling point/boiling range Flash Point		Remarks • Methods No information available No information available No information available
Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit	46 °C / 115 °F	No information available No information available No information available
lower flammability limit Vapor pressure Vapor density Specific Gravity Water solubility		No information available No information available No information available No information available No information available
Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature	> 22 mm2/s	No information available No information available No information available No information available
Viscosity, kinematic Viscosity, dynamic Explosive properties Oxidizing Properties	> 22 111112/5	No information available No information available No information available
9.2 Other information Volatile organic compounds (VOC) content	330 g/L	

21.12 lb/gal

## 10. Stability and Reactivity

#### 10.1 Reactivity

Density

No dangerous reaction known under conditions of normal use

## 10.2 Chemical stability

Stable under recommended storage conditions

#### 10.3 Possibility of hazardous reactions

None under normal processing.

## 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

#### 10.5 Incompatible Materials

No materials to be especially mentioned.

## 10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

## 11. Toxicological information

## 11.1 Acute toxicity

Numerical measures of toxicity: Product Information

#### The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity	< 1% of the mixture consists of ingredient(s) of unknown toxicity
Oral LD50	712.00 mg/kg
LC50 (Vapor)	340.00 mg/l

#### Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Cuprous oxide 1317-39-1	470 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 5 mg/L (Rat)4 h
HEAVY AROMATIC NAPHTHA 64742-94-5	5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m³(Rat)4 h
Xylene 1330-20-7	3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	10000 mg/kg (Rat)	-	-
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
N-METHYL-2-PYRROLIDONE 872-50-4	3598 mg/kg (Rat)	= 8 g/kg (Rabbit)	> 5100 ppm (Rat)4 h

## 11.2 Information on toxicological effects

## Skin corrosion/irritation

Product Information

• No information available Component Information

No information available

## Eye damage/irritation

No information available
 Component Information
 No information available

## Respiratory or skin sensitization

Product Information
No information available
Component Information
No information available

## Germ cell mutagenicity

Product Information • No information available <u>Component Information</u> • No information available

## Carcinogenicity

Product Information • No information available <u>Component Information</u> Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	
SILICA (CRYSTALLINE-CRISTOBA LITE) 14464-46-1	A2	Group 1	-	
Ethylbenzene 100-41-4	-	Group 2B	-	

## **Reproductive toxicity**

Product Information • No information available <u>Component Information</u> • No information available

#### **STOT - single exposure** No information available

STOT - repeated exposure

No information available

## Other adverse effects

Product Information
No information available
Component Information
No information available

#### Aspiration hazard

- Product Information • No information available <u>Component Information</u>
- No information available

## 12. Ecological information

## 12.1 Toxicity

#### Ecotoxicity

No information available

3.02048 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Cuprous oxide 1317-39-1	EC50: 96 h Desmodesmus subspicatus 65 mg/L EC50: 96 h Pseudokirchneriella subcapitata 0.021 - 0.037 mg/L EC50: 96 h Pseudokirchneriella subcapitata 0.055 - 0.076 mg/L static	-	EC50: 48 h Daphnia magna 0.51 mg/L
HEAVY AROMATIC NAPHTHA 64742-94-5	-	LC50: 96 h Pimephales promelas 19 mg/L static LC50: 96 h Oncorhynchus mykiss 2.34 mg/L LC50: 96 h Lepomis macrochirus 1740 mg/L static LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Pimephales promelas 41 mg/L	EC50: 48 h Daphnia magna 0.95 mg/L
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L

1330-20-7		23.53 - 29.97 mg/L static LC50: 96 h Cyprinus carpio 780 mg/L semi-static LC50: 96 h Cyprinus carpio 780 mg/L LC50: 96 h Poecilia reticulata 30.26 - 40.75 mg/L static LC50: 96 h Pimephales promelas 13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L LC50: 96 h Lepomis macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis	LC50: 48 h Gammarus lacustris 0.6 mg/L
		macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591 mg/L static	
Copper (as Cu Dust & Mists) 7440-50-8	EC50: 72 h Pseudokirchneriella subcapitata 0.0426 - 0.0535 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 0.031 - 0.054 mg/L static	LC50: 96 h Pimephales promelas 0.0068 - 0.0156 mg/L LC50: 96 h Pimephales promelas 0.3 mg/L static LC50: 96 h Pimephales promelas 0.2 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 0.052 mg/L flow-through LC50: 96 h Lepomis macrochirus 1.25 mg/L static LC50: 96 h Cyprinus carpio 0.3 mg/L semi-static LC50: 96 h Cyprinus carpio 0.8 mg/L static LC50: 96 h Poecilia reticulata 0.112 mg/L flow-through	EC50: 48 h Daphnia magna 0.03 mg/L Static
Ethylbenzene 100-41-4	EC50: 72 h Pseudokirchneriella subcapitata 4.6 mg/L EC50: 96 h Pseudokirchneriella subcapitata 438 mg/L EC50: 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L static	LC50: 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L static LC50: 96 h Oncorhynchus mykiss 4.2 mg/L semi-static LC50: 96 h Pimephales promelas 7.55 - 11 mg/L flow-through LC50: 96 h Lepomis macrochirus 32 mg/L static LC50: 96 h Pimephales promelas 9.1 - 15.6 mg/L static LC50: 96 h Poecilia reticulata 9.6 mg/L static	EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L
N-METHYL-2-PYRROLIDONE 872-50-4	EC50: 72 h Desmodesmus subspicatus 500 mg/L	LC50: 96 h Lepomis macrochirus 832 mg/L static LC50: 96 h Pimephales promelas 1072 mg/L static LC50: 96 h Poecilia reticulata 1400 mg/L static	EC50: 48 h Daphnia magna 4897 mg/L

## 12.2 Persistence and degradability

No information available.

## 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
HEAVY AROMATIC NAPHTHA 64742-94-5	6.1
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
N-METHYL-2-PYRROLIDONE 872-50-4	-0.46

## 12.4 Mobility in soil

No information available.

## 12.5 Other adverse effects

No information available

## **13. Disposal Considerations**

#### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information			
Note DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)"			
DOT	Not regulated (If shipped in NON BULK packaging by ground transport)		
MEX	no data available		
IMDG Proper shipping name	UN1263, Paint, 3, III		
IATA Proper shipping name	UN1263, Paint, 3, III		

## **15. Regulatory information**

15.1 International Inventories

TSCA DSL EINECS/ELINCS	Complies Complies -
ENCS	-
IECSC	-
KECL	-
PICCS	-
AICS	-
NZIOC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

## 15.2 U.S. Federal Regulations

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Cuprous oxide 1317-39-1	1.0
Xylene 1330-20-7	1.0
Cupric Oxide 1317-38-0	1.0

Copper (as Cu Dust & Mists) 7440-50-8	1.0
Ethylbenzene 100-41-4	0.1

## 15.3 Pesticide Information

#### U.S. EPA Pesticide Information

EPA Pesticide Registration Number 60061-49

#### EPA Statement

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

#### **EPA Pesticide Label**

WARNING. May be fatal if swallowed or inhaled. Causes moderate eye irritation. Harmful if absorbed through skin.

## 15.4 U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
N-METHYL-2-PYRROLIDONE - 872-50-4	Developmental
Toluene - 108-88-3	Developmental Female Reproductive
NAPHTHALENE - 91-20-3	Carcinogen
CUMENE - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

16. Other information				
NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and chemical hazards
<u>HMIS</u>	Health Hazard 2*	Flammability 2	Physical Hazard 0	Personal protection X

#### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists) Ceiling (C) DOT (Department of Transportation) EPA (Environmental Protection Agency) IARC (International Agency for Research on Cancer) International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG) NIOSH (National Institute for Occupational Safety and Health) NTP (National Toxicology Program) OSHA (Occupational Safety and Health Administration of the US Department of Labor) PEL (Permissible Exposure Limit) Reportable Quantity (RQ) Skin designation (S\*) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) TWA (time-weighted average)

Revision Date18-Nov-2015Revision Note18-Nov-2015No information available18-Nov-2015Disclaimer18-Nov-2015

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

## **End of Safety Data Sheet**