SAFETY DATA SHEET



Revision Date 01-Dec-2015 Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Product code Pettit EZ-Poxy Modern Polyurethane Topside Paint 3705 Mist Gray 1370500

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Restrictions on use Paint Read label instructions and SDS

1.3 Details of the supplier of the safety data sheet

| Su | pr | olie | er |
|----|----|------|----|
| | | | |

Kop-Coat, Inc. Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

| Skin sensitization | Category 1 |
|--|------------|
| Carcinogenicity | Category 2 |
| Specific target organ toxicity (repeated exposure) | Category 1 |
| Flammable liquids | Category 3 |

2.2 Label elements

Signal Word Danger

Hazard Statements

May cause an allergic skin reaction Suspected of causing cancer Causes damage to organs through prolonged or repeated exposure Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Contaminated work clothing must not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC) Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

1.33911724% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance Not applicable Mixture

| Chemical Name | CAS-No | Weight % |
|------------------|------------|----------|
| Titanium dioxide | 13463-67-7 | 30 - 40 |

1370500 - Pettit EZ-Poxy Modern Polyurethane Topside Paint 3705 Mist Gray

| 64742-47-8 | 10 - 20 |
|------------|--|
| 8052-41-3 | 5 - 10 |
| 64742-88-7 | 1 - 5 |
| 8008-20-6 | 1 - 5 |
| 21645-51-2 | 1 - 5 |
| 100-41-4 | < 1 |
| 96-29-7 | < 1 |
| | 8052-41-3 64742-88-7 8008-20-6 21645-51-2 100-41-4 |

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

| General advice | For further assistance, contact your local Poison Control Center. | | |
|--|--|--|--|
| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice. | | |
| Skin contact | Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice. | | |
| Inhalation | Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice. | | |
| Ingestion | Rinse mouth. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center immediately. | | |
| 4.2 Most important symptoms and effects, both acute and delayed | | | |
| Symptoms | See Section 2.2, Label Elements and/or Section 11, Toxicological effects. | | |
| 4.3 Indication of any immediate medical attention and special treatment needed | | | |
| Notes to physician | There is no specific antidote for effects from overexposure to this material. Treat symptomatically. | | |
| 5 Fire-Fighting Measures | | | |

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Yes.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

| Methods for Containment | Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. |
|-------------------------|--|
| Methods for cleaning up | Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools and equipment. |

7. Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling | Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking. | | | |
|-------------------------------------|--|--|--|--|
| Hygiene measures | Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. | | | |
| 7.2 Conditions for safe storage, in | cluding any incompatibilities | | | |
| Storage Conditions | Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations. | | | |
| Materials to Avoid | No materials to be especially mentioned. | | | |
| | 8. Exposure controls/personal protection | | | |

8.1 Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | British Columbia | Alberta | Quebec | Ontario TWAEV |
|---|---|---|---|--|--|----------------------------|
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | TWA: 10 mg/m ³ TWA: 3 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ |
| Distillates, petroleum, hydrotreated light 64742-47-8 | - | - | TWA: 200 mg/m³ Skin | | | |
| Stoddard Solvent 8052-41-3 | TWA: 100 ppm | TWA: 500 ppm TWA: 2900 mg/m ³ | TWA: 290 mg/m ³ STEL: 580 mg/m ³ | TWA: 100 ppm TWA: 572 mg/m ³ | TWA: 100 ppm TWA: 525 mg/m ³ | TWA: 525 mg/m ³ |
| Kerosene 8008-20-6 | TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S* | - | TWA: 200 mg/m³ Skin | TWA: 200 mg/m³ Skin | | TWA: 200 mg/m³ Skin |
| Aluminium Hydroxide 21645-51-2 | TWA: 1 mg/m ³ respirable fraction | - | TWA: 1.0 mg/m ³ | | | TWA: 1 mg/m ³ |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m³ | TWA: 20 ppm | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³ | TWA: 20 ppm |

8.2 Appropriate engineering controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits.

8.3 Individual protection measures, such as personal protective equipment

| Eye/Face Protection | Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles. Face-shield. |
|--------------------------|---|
| Skin and body protection | Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Wear suitable protective clothing. Remove and wash contaminated clothing before re-use. |
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. |
| Hygiene measures | See section 7 for more information |

9. Physical and chemical properties

| <u>9.1 Information on basic physical a</u> Physical state Appearance Color Odor Odor Threshold | Ind chemical properties Liquid No information available Gray Hydrocarbon-like No information available | |
|---|---|---|
| <u>Property</u> pH Melting/freezing point Boiling point/boiling range | Values_ | Remarks • Methods No information available No information available No information available |
| Flash Point Evaporation rate Flammability (solid, gas) | 45 °C / 113 °F | No information available No information available |
| Flammability Limits in Air upper flammability limit lower flammability limit | | No information available No information available |
| Vapor pressure Vapor density Specific Gravity | | No information available No information available No information available |
| Water solubility Solubility in other solvents | | No information available No information available |
| Partition coefficient Autoignition temperature Decomposition temperature | | No information available No information available No information available |
| Viscosity, kinematic Viscosity, dynamic | > 22 mm2/s | No information available |
| Explosive properties Oxidizing Properties | | No information available No information available |
| <u>9.2 Other information</u> Volatile organic compounds (VOC) content | 377 g/L | |

10.5 lb/gal

10. Stability and Reactivity

10.1 Reactivity

Density

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable under recommended storage conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

10.5 Incompatible Materials

No materials to be especially mentioned.

10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 1.33911724% of the mixture consists of ingredient(s) of unknown toxicity

Dermal LD50 86,111.00 mg/kg

Numerical measures of toxicity: Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|-------------------|------------------------|----------------------|
| Titanium dioxide 13463-67-7 | 10000 mg/kg (Rat) | - | - |
| Distillates, petroleum, hydrotreated light 64742-47-8 | 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat)4 h |
| ALIPHATIC NAPHTHA 64742-88-7 | 5000 mg/kg (Rat) | = 3000 mg/kg (Rabbit) | > 5.28 mg/L (Rat)4 h |
| Kerosene 8008-20-6 | 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.28 mg/L (Rat)4 h |
| Aluminium Hydroxide 21645-51-2 | 5000 mg/kg (Rat) | - | - |
| Ethylbenzene 100-41-4 | 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.2 mg/L (Rat)4 h |
| Methyl ethyl ketoxime 96-29-7 | 930 mg/kg (Rat) | = 0.2 mg/kg (Rabbit) | = 20 mg/L (Rat)4 h |

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information • No information available <u>Component Information</u>

No information available

Eye damage/irritation

Product Information • No information available

Component Information

· No information available

Respiratory or skin sensitization

Product Information
No information available
Component Information
No information available

Germ cell mutagenicity

Product Information • No information available <u>Component Information</u> • No information available

Carcinogenicity

Product Information

• The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

Contains a known or suspected carcinogen

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--------------------------------|-------|----------|-----|------|
| Titanium dioxide 13463-67-7 | - | Group 2B | - | |
| Ethylbenzene 100-41-4 | - | Group 2B | - | |

Reproductive toxicity

Product Information

No information available

Component Information

No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effects

Product Information • No information available <u>Component Information</u> • No information available

Aspiration hazard

Product Information • No information available

Component Information

No information available

12. Ecological information

12.1 Toxicity

Ecotoxicity

No information available

3.33175 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia and other aquatic invertebrates |
|---|--|---|--|
| Distillates, petroleum, hydrotreated light 64742-47-8 | - | LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Lepomis macrochirus 2.2 mg/L static LC50: 96 h Oncorhynchus mykiss 2.4 mg/L static | - |
| ALIPHATIC NAPHTHA 64742-88-7 | EC50: 96 h Pseudokirchneriella subcapitata 450 mg/L | LC50: 96 h Pimephales promelas 800 mg/L static | EC50: 48 h Daphnia magna 100 mg/L |
| Ethylbenzene 100-41-4 | , | | EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L |

| Methyl ethyl ketoxime | EC50: 72 h Desmodesmus | LC50: 96 h Pimephales promelas | EC50: 48 h Daphnia magna 750 |
|-----------------------|------------------------|---|------------------------------|
| 96-29-7 | subspicatus 83 mg/L | 777 - 914 mg/L flow-through LC50: | mg/L |
| | | 96 h Poecilia reticulata 760 mg/L static | |

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

| Chemical Name | log Pow |
|----------------------------------|---------|
| Ethylbenzene 100-41-4 | 3.118 |
| Methyl ethyl ketoxime 96-29-7 | 0.65 |

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste treatment methods

15.1 International Inventories

Disposal should be in accordance with applicable regional, national and local laws and regulations.

| 14. Transport Information | | | |
|------------------------------|--|--|--|
| Note | DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2)" | | |
| DOT | Not regulated (If shipped in NON BULK packaging by ground transport) | | |
| MEX | no data available | | |
| IMDG Proper shipping name | UN1263, Paint, 3, III | | |
| IATA Proper shipping name | UN1263, Paint, 3, III | | |

15. Regulatory information

| TSCA | Complies |
|---------------|----------|
| DSL | - |
| EINECS/ELINCS | - |
| ENCS | - |
| IECSC | - |
| KECL | - |
| PICCS | - |
| AICS | - |
| NZIOC | - |

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances NZIOC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name | SARA 313 - Threshold Values % | |
|--------------------------|-------------------------------|--|
| Ethylbenzene 100-41-4 | 0.1 | |

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|---|--|
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Ethylbenzene - 100-41-4 | Carcinogen |
| Crystalline silica (Quartz) (Respirable) - 14808-60-7 | Carcinogen |
| Benzene - 71-43-2 | Carcinogen Developmental Male Reproductive |
| Toluene - 108-88-3 | Developmental Female Reproductive |

| 16. Other information | | | | |
|-----------------------|------------------|----------------|-------------------|-------------------------------|
| NFPA | Health Hazard 2 | Flammability 2 | Instability 0 | Physical and chemical hazards |
| HMIS | Health Hazard 2* | Flammability 2 | Physical Hazard 0 | Personal protection X |

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists) Ceiling (C) DOT (Department of Transportation) EPA (Environmental Protection Agency) IARC (International Agency for Research on Cancer) International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG) NIOSH (National Institute for Occupational Safety and Health) NTP (National Toxicology Program) OSHA (Occupational Safety and Health Administration of the US Department of Labor) PEL (Permissible Exposure Limit) Reportable Quantity (RQ) Skin designation (S*) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) TWA (time-weighted average)

Revision Date Revision Note No information available Disclaimer 01-Dec-2015

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet