SAFETY DATA SHEET



Revision Date 05-Nov-2015

Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Pettit XL Hydrocoat ECO 1204 Blue

Product code 1120405

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Paint/Paint Related Material No information available

1.3 Details of the supplier of the safety data sheet

Supplier Kop-Coat, Inc./ Pettit Marine Paint

Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA

Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Oral	Category 4
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A

2.2 Label elements

Signal Word

Danger

Hazard Statements

Harmful if swallowed Causes serious eye damage May cause cancer



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

< 1% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

This product is a mixture. Health hazard information is based on its components. Not applicable **Mixture**_

Chemical Name	CAS-No	Weight %
Barium Sulfate	7727-43-7	20 - 30
Titanium dioxide	13463-67-7	10 - 20
Zinc oxide	1314-13-2	5 - 10
Zinc pyrithione	13463-41-7	1 - 5
Tripropylene glycol monomethyl ether	25498-49-1	1 - 5
Calcined Kaolin	92704-41-1	1 - 5
POLYTETRAFLUOROETHYLENE	9002-84-0	1 - 5
C.I. Pigment Blue 15	147-14-8	1 - 5
Crystalline silica (Quartz) (Respirable)	14808-60-7	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice Show this safety data sheet to the doctor in attendance. When symptoms persist or in all

cases of doubt seek medical advice.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Call a physician or poison control center

immediately.

Skin contact Call a poison control center or doctor for treatment advice. Wash off immediately with plenty

of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash

contaminated clothing before reuse.

Inhalation Move victim to fresh air. Apply artificial respiration if victim is not breathing. Call a physician

or poison control center immediately.

Ingestion Call a physician or poison control center immediately. If swallowed, DO NOT induce

vomiting unless directed to do so by medical personnel. Gently wipe or rinse the inside of

the mouth with water. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physicianThere is no specific antidote for effects from overexposure to this material. Treat

symptomatically.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, fog, Carbon dioxide (CO₂), foam or dry chemical. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media None known based on information supplied.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Thermal decomposition can lead to release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus and full protective gear. Thoroughly decontaminate all protective equipment after use. Use water spray to cool fire-exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas. Use personal protective equipment. Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section

8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances

created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

6.2 Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Clean contaminated surface thoroughly.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Handle in

accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product

residue or vapor.

Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when Hygiene measures

using this product. Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled **Storage Conditions**

containers. Keep away from food, drink and animal feedingstuffs. Keep from freezing.

Materials to Avoid No materials to be especially mentioned.

8. Exposure controls/personal protection

8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Barium Sulfate 7727-43-7	TWA: 5 mg/m³ inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ TWA: 3 mg/m³	TWA: 10 mg/m³	TWA: 10 mg/m³ TWA: 5 mg/m³	TWA: 10 mg/m³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
Zinc oxide 1314-13-2	STEL: 10 mg/m³ respirable fraction TWA: 2 mg/m³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 2 mg/m³ STEL: 10 mg/m³	TWA: 2 mg/m³ STEL: 10 mg/m³	TWA: 10 mg/m³ TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 2 mg/m ³ STEL: 10 mg/m ³
POLYTETRAFLUORO ETHYLENE 9002-84-0	-	-			TWA: 2.5 mg/m ³	
C.I. Pigment Blue 15 147-14-8	TWA: 1 mg/m³ Cu dust and mist	-				
Crystalline silica (Quartz) (Respirable)	TWA: 0.025 mg/m³ respirable fraction	: (30)/(%SiO2 + 2) mg/m³ TWA total	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³

05-Nov-2015 - 1120405 - 1 - AGHS - English -

14808-60-7	dust		
	: (250)/(%SiO2 +		
	5) mppcf TWA		
	respirable fraction		
	: (10)/(%SiO2 + 2)		
	mg/m³ TWA		
	respirable fraction		

8.2 Appropriate engineering controls

Engineering Measures None under normal use conditions. Ensure adequate ventilation, especially in confined

areas. Where reasonably practicable this should be achieved by the use of local exhaust

ventilation and good general extraction.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Remove and wash contaminated clothing before re-use. Wear protective gloves/ protective

clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn.

Hygiene measures See section 7 for more information

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid Viscous liquid

Color Blue

OdorHydrocarbon-likeOdor ThresholdNo information available

PropertyValuesRemarks • MethodspHNo information availableMelting/freezing pointNo information available

Boiling point/boiling range

No information available

Flash Point $> 98 \, ^{\circ}\text{C} \, / > 208 \, ^{\circ}\text{F}$

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability (solid, gas) No information available Flammability Limits in Air

 upper flammability limit
 No information available

 lower flammability limit
 No information available

 Yapor pressure
 No information available

Vapor pressureNo information availableVapor densityNo information available

Specific Gravity 1.627

Water solubility

Solubility in other solvents

Partition coefficient

Autoignition temperature

Decomposition temperature

No information available
No information available
No information available
No information available

Viscosity, kinematic > 21 mm2/s

Viscosity, dynamic No information available

Explosive properties

Oxidizing Properties

No information available
No information available

9.2 Other information

Volatile organic compounds (VOC) < 150 g/L

content

Density 13.55 lb/gal

10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

No information available.

10.5 Incompatible Materials

No materials to be especially mentioned.

10.6 Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity < 1% of the mixture consists of ingredient(s) of unknown toxicity

Oral LD50 425.00 mg/kg **LC50 (Dust/Mist)** 23.00 mg/l

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Barium Sulfate 7727-43-7	> 5005 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	10000 mg/kg (Rat)	-	-
Zinc oxide 1314-13-2	5000 mg/kg (Rat)	-	-
Zinc pyrithione 13463-41-7	269 mg/kg (rat)	> 2000 mg/kg (rabbit)	= 1.03 mg/L (Rat) 4 h
Tripropylene glycol monomethyl ether 25498-49-1	3184 mg/kg (Rat)	= 15440 mg/kg (Rabbit)	-
Calcined Kaolin 92704-41-1	2000 mg/kg (Rat)	-	-
Crystalline silica (Quartz) (Respirable) 14808-60-7	500 mg/kg (Rat)	-	-

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

· No information available

Component Information

No information available

Eye damage/irritation

Product Information

· No information available

Component Information

· No information available

Respiratory or skin sensitization

Product Information

No information available

Component Information

• No information available

Germ cell mutagenicity

Product Information

No information available

Component Information

· No information available

Carcinogenicity

Product Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen Component Information
- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	
Crystalline silica (Quartz) (Respirable) 14808-60-7	A2	Group 1	Known	

Reproductive toxicity

Product Information

No information available

Component Information

• No information available

STOT - single exposure

No information available

STOT - repeated exposure

· No information available

Other adverse effects

Product Information

- · No information available
- Component Information
- No information available

Aspiration hazard

Product Information

- No information available
- **Component Information**
- · No information available

12. Ecological information

12.1 Toxicity

Ecotoxicity No information available

33.0618005 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Tripropylene glycol monomethyl ether 25498-49-1	-	LC50: 96 h Pimephales promelas 11619 mg/L static	EC50: 48 h Daphnia magna 10 mg/L
Calcined Kaolin 92704-41-1	EC50: 72 h Desmodesmus subspicatus 100 mg/L	LC50: 96 h Oncorhynchus mykiss 100 mg/L semi-static	EC50: 48 h Daphnia magna 1 mg/L

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
C.I. Pigment Blue 15 147-14-8	6.6

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information

DOT Not regulated

MEX no data available

IMDG

Proper shipping name UN3082, Environmentally hazardous substance, liquid, n.o.s. (Tralopyril, zinc pyrithione), 9,

PG III, Marine Pollutant

IATA

Proper shipping name UN3082, Environmentally hazardous substance, liquid, n.o.s. (Tralopyril, zinc pyrithione), 9,

PG III

15. Regulatory information

15.1 International Inventories

TSCA Complies

05-Nov-2015 - 1120405 - 1 - AGHS - English -

DSL -

EINECS/ELINCS ENCS IECSC KECL PICCS AICS NZIOC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Barium Sulfate 7727-43-7	1.0
Zinc oxide 1314-13-2	1.0
Zinc pyrithione 13463-41-7	1.0
Tripropylene glycol monomethyl ether 25498-49-1	1.0
C.I. Pigment Blue 15 147-14-8	1.0

15.3 Pesticide Information

U.S. EPA Pesticide Information

EPA Pesticide Registration Number 60061-137

EPA Statement

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

EPA Pesticide Label

DANGER. Causes substantial but temporary eye injury. Causes skin irritation. May pose an aspiration pneumonia hazard.

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Titanium dioxide - 13463-67-7	Carcinogen
Crystalline silica (Quartz) (Respirable) - 14808-60-7	Carcinogen
Acetaldehyde - 75-07-0	Carcinogen
Cadmium - 7440-43-9	Carcinogen Developmental Male Reproductive
Lead - 7439-92-1	Carcinogen

05-Nov-2015 - 1120405 - 1 - AGHS - English -

	Developmental Female Reproductive Male Reproductive
METHANOL - 67-56-1	Developmental
Acrylamide - 79-06-1	Carcinogen Developmental Male Reproductive

16. Other information

NFPA Health Hazard 2 Flammability 1 Instability 0 Physical and chemical hazards
HMIS Health Hazard 2* Flammability 1 Physical Hazard 0 Personal protection X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date

05-Nov-2015

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet