

SAFETY DATA SHEET

PETTIT



Revision Date 17-Nov-2016
Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name 6455 METAL PRIMER - PART A
Product code 1645500

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Paint/Paint Related Material
Restrictions on use Read label instructions and SDS

1.3 Details of the supplier of the safety data sheet

Supplier Kop-Coat, Inc. / Pettit Marine Paint
Marine Group
36 Pine Street
Rockaway, NJ 07866
1-800-221-4466

1.4 Emergency telephone number

Emergency telephone number Chemtrec: +1 703-527-3887 ex-USA
Chemtrec: 1-800-424-9300 USA

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3 - (H335,H336)
Flammable liquids	Category 3

2.2 Label elements

Signal Word

Danger

Hazard Statements

Harmful if swallowed

Causes skin irritation

Causes serious eye damage

May cause an allergic skin reaction

May cause cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity < 1% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

Not applicable

Mixture

Chemical Name	CAS-No	Weight %
Isopropyl alcohol	67-63-0	50 - 60
n-Butanol	71-36-3	20 - 30
Pentazinc chromate octahydroxide	49663-84-5	5 - 10
Polyvinyl butyral resin	63148-65-2	5 - 10
Carbon black	1333-86-4	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician or poison control center immediately.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a physician or poison control center immediately.
Inhalation	Move victim to fresh air. If not breathing, give artificial respiration. Keep victim warm and quiet. Call a physician or poison control center immediately.
Ingestion	Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Gently wipe or rinse the inside of the mouth with water. Never give fluids if the victim is unconscious or having convulsions. Call a physician or poison control center immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician There is no specific antidote for effects from overexposure to this material. Treat symptomatically.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

5.2 Special hazards arising from the substance or mixture

Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

Explosion Data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Yes.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished. Corrosive hazard. Wear protective gloves/clothing and eye/face protection.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation, especially in confined areas. Keep people away from and upwind of spill/leak. Wear protective gloves/clothing and eye/face protection. Thoroughly decontaminate all protective equipment after use. Ensure adequate ventilation, especially in confined areas.

6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. Prevent further leakage or spillage if safe to do so. See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment	Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Dike to collect large liquid spills. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
Methods for cleaning up	Take up with sand, earth or other noncombustible absorbent material. Clean contaminated surface thoroughly.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	Do not get in eyes, on skin, or on clothing. Ground and bond containers when transferring material. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Handle in accordance with good industrial hygiene and safety practice. No smoking.
Hygiene measures	Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Handle in accordance

with good industrial hygiene and safety practice.

7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedings. Store in accordance with local regulations.

Materials to Avoid No materials to be especially mentioned.

8. Exposure controls/personal protection

8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm TWA: 492 mg/m ³ STEL: 400 ppm STEL: 984 mg/m ³	TWA: 400 ppm TWA: 985 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³	TWA: 200 ppm STEL: 400 ppm
n-Butanol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³	TWA: 15 ppm Ceiling: 30 ppm	TWA: 20 ppm TWA: 60 mg/m ³	Ceiling: 50 ppm Ceiling: 152 mg/m ³ Skin	TWA: 20 ppm
Pentazinc chromate octahydroxide 49663-84-5	-	TWA: 5 µg/m ³ Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect		TWA: 0.01 mg/m ³ TWA: 0.5 mg/m ³		TWA: 0.01 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³

8.2 Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Apply technical measures to comply with the occupational exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.

Skin and body protection Nitrile rubber. Neoprene gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Long sleeved clothing. Chemical resistant apron. Protective shoes or boots.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. In case of mist, spray or aerosol exposure wear suitable respiratory protection equipment.

Hygiene measures See section 7 for more information

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available
Color	dark green
Odor	Alcohol
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH		No information available
Melting/freezing point		No information available
Boiling point/boiling range	83 °C / 181 °F	No information available for Isopropanol (83 deg C)
Flash Point	23 °C / 73 °F	
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		
upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure		No information available
Vapor density		No information available
Specific Gravity		No information available
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic	> 22 mm ² /s	
Viscosity, dynamic		No information available
Explosive properties		No information available
Oxidizing Properties		No information available

9.2 Other information

Volatile organic compounds (VOC) content	712 g/L Coating VOC
Density	7.43 lb/gal

10. Stability and Reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use

10.2 Chemical stability

Stable under recommended storage conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

None known based on information supplied.

10.5 Incompatible Materials

No materials to be especially mentioned.

10.6 Hazardous Decomposition Products

Thermal decomposition can lead to release of toxic/corrosive gases and vapors.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity < 1% of the mixture consists of ingredient(s) of unknown toxicity

Oral LD50 1,362.00 mg/kg
Dermal LD50 3,335.00 mg/kg

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol 67-63-0	5840 mg/kg (Rat)	= 13,900 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
n-Butanol 71-36-3	700 mg/kg (Rat)	= 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

- No information available

Component Information

- No information available

Serious eye damage/eye irritation

Product Information

- No information available

Component Information

- No information available

Respiratory or skin sensitization

Product Information

- No information available

Component Information

- No information available

Germ cell mutagenicity

Product Information

- No information available

Component Information

- No information available

Carcinogenicity

Product Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropyl alcohol 67-63-0	-	Group 3	-	
Pentazinc chromate octahydroxide 49663-84-5	-	Group 1	Known	Group 1
Carbon black 1333-86-4	-	Group 2B	-	

Reproductive toxicityProduct Information

- No information available

Component Information

- No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effectsProduct Information

- No information available

Component Information

- No information available

Aspiration hazardProduct Information

- No information available

Component Information

- No information available

12. Ecological information

12.1 ToxicityEcotoxicity

No information available

8.2017 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Isopropyl alcohol 67-63-0	EC50: 96 h Desmodesmus subspicatus 1000 mg/L EC50: 72 h Desmodesmus subspicatus 1000 mg/L	LC50: 96 h Pimephales promelas 9640 mg/L flow-through LC50: 96 h Pimephales promelas 11130 mg/L static LC50: 96 h Lepomis macrochirus 1400000 µg/L	EC50: 48 h Daphnia magna 13299 mg/L
n-Butanol 71-36-3	EC50: 96 h Desmodesmus subspicatus 500 mg/L EC50: 72 h Desmodesmus subspicatus 500 mg/L	LC50: 96 h Pimephales promelas 1730 - 1910 mg/L static LC50: 96 h Pimephales promelas 1740 mg/L flow-through LC50: 96 h Lepomis macrochirus 100000 - 500000 µg/L static LC50: 96 h Pimephales promelas 1910000 µg/L static	EC50: 48 h Daphnia magna 1983 mg/L EC50: 48 h Daphnia magna 1897 - 2072 mg/L Static

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Isopropyl alcohol 67-63-0	0.05
n-Butanol 71-36-3	0.785

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. Transport Information

<u>DOT</u>	Limited quantity DOT - Special Provision 149: UN1263, Paint or Paint related material, PGI: When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in CFR 49. 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).
Proper shipping name	UN1263, Paint related material, 3, PG II
<u>MEX</u>	no data available
<u>IMDG</u>	
Proper shipping name	UN1263, Paint related material, 3, PG II
<u>IATA</u>	
Proper shipping name	UN1263, Paint related material, 3, PG II

15. Regulatory information

15.1 International Inventories

TSCA	Complies
DSL	Complies
EINECS/ELINCS	-
ENCS	-
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	-
NZIoC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Isopropyl alcohol 67-63-0	1.0
n-Butanol 71-36-3	1.0
Pentazinc chromate octahydroxide 49663-84-5	0.1 1.0

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Pentazinc chromate octahydroxide - 49663-84-5	Carcinogen Developmental Female Reproductive Male Reproductive
Carbon black - 1333-86-4	Carcinogen
Crystalline silica (Quartz) (Respirable) - 14808-60-7	Carcinogen

16. Other information

NFPA	Health Hazard 3	Flammability 3	Instability 0	Physical and chemical hazards - Personal protection X
HMIS	Health Hazard 3*	Flammability 3	Physical Hazard 0	

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date 17-Nov-2016

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet