



# SAFETY DATA SHEET

## 1. Product Identification

---

Product name	EZ Bond Part A	
SDS Number	1708020	
Product type	Epoxy polymer mixture.	
Recommended use of the chemical and restrictions on use	Directed at, but not limited to, the adhesion of similar and dissimilar substrates.	
Restrictions	None known.	
<b>Manufacturer/Supplier information</b>		
Company name	Kop-Coat Inc./Kop Coat Marine	
Address	36 Pine Street Rockaway, NJ 07866 United States	
Telephone	973-625-3100	
Emergency Contact	CHEMTREC (U.S. and CANADA)	1-800-424-9300
	CHEMTREC (Outside the U.S.)	1-703-527-0585

## 2. Hazard(s) Identification

---

**Classification of substance or mixture/Signal word**

WARNING.  
Skin Irritation Category 2  
Eye Irritation Category 2  
Skin Sensitization Category 1

**GHS Label Elements**  
**Hazard Pictograms**



**Hazard statements**

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

**Precautionary Statements**  
**Prevention**

P280 Wear protective gloves. Wear eye or face protection.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.

**Response**

P308 + P313 If exposed or concerned: Get medical attention.

**Storage**

P401 Store above 32 °F / 0 °C

**Disposal**

P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazards not otherwise classified (HNOC)**

None Available.

### 3. Composition/Information On Ingredients

---

Chemical Name	CAS Number	Content (%)
Diglycidyl Ether of Bisphenol A	25068-38-6	90-95 %

### 4. First-Aid Measures

---

<b>Inhalation</b>	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing and shoes and wipe excess off skin. Flush skin with water. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather articles (shoes) cannot be decontaminated and should be destroyed.
<b>Eye contact</b>	Flush with water for 15 minutes holding eye lids open. Seek medical attention.
<b>Ingestion</b>	Do not give liquids if victim is unconscious or very drowsy. Otherwise, give no more than 2 glasses of water and induce vomiting by giving 2 tablespoons syrup of ipecac (1 tablespoon and 1 glass of water for child). If ipecac is unavailable, give 2 glasses of water and induce vomiting by touching finger to back of throat. Keep head below hips while vomiting. Get medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Burns. Irritation. Pre-existing skin conditions may be aggravated by prolonged or repeated contact. Persons with sensitive airways (e.g., asthmatics) may be sensitive to vapors.
<b>Indication of immediate medical attention and special treatment needed</b>	Treat symptoms as they appear.

### 5. Fire-Fighting Measures

---

<b>Suitable extinguishing media</b>	Foam, carbon dioxide, dry chemical, water fog.
<b>Unsuitable extinguishing media</b>	None known
<b>Specific hazards arising from the chemical</b>	Potential skin irritation.
<b>Special protective equipment and precautions for fire-fighters</b>	When fighting chemical fires wear full protective equipment with self-contained breathing apparatus. Water spray may be used to cool fire-exposed containers. Toxic fumes may be evolved when this substance is burned.
Fire-fighting equipment/instructions	Full fire suit and self-contained breathing apparatus.
Specific methods	Water spray may be used to cool fire-exposed containers. Toxic fumes may be evolved when this substance is burned.
General fire hazards	Epoxy in mass can create exotherm.

### 6. Accidental Release Measures

---

<b>Personal precautions</b>	Wear proper personal protective equipment (PPE). Avoid direct contact with material.
<b>Protective equipment</b>	Proper PPE includes: disposable gloves, eye protection and skin protection.
<b>Emergency procedures</b>	If material is spilled, avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete.

**Methods and materials for containment/cleanup**

Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth, sawdust or other absorbent, and shoveled into disposal container.

**Environmental precautions**

Skin sensitizer, harmful to aquatic life. Avoid dispersal of spilled material, contact with soil, waterways, drains and sewers.

## 7. Handling And Storage

---

**Precautions for safe handling**

Always wear protective, disposable gloves when handling epoxy products to prevent exposure.

**Precautions/Recommendations for safe/proper storage**

Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products from sitting and below freezing temperatures.

**Chemical incompatibilities**

None known.

## 8. Exposure Controls/Personal Protection

---

**Permissible exposure limit (OSHA)**

None established

**Threshold limit value (ACGIH)**

None established

**Biological Toxicology**

Not available

**Appropriate engineering controls**

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures/Personal protective equipment**

Eye/face protection

Splash proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy to avoid dust in eyes.

Hand protection

Always wear impervious gloves, neoprene, vinyl or rubber.

Skin protection

Wear clean, body-covering clothing to avoid skin contact.

Respiratory protection

Use a NIOSH approved respiratory device when sanding cured epoxy to prevent dust in lungs.

General hygiene during/after use

Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

## 9. Physical And Chemical Properties

---

**Chemical family**

Epoxy Resin

**Appearance**

Blue viscous paste

**Physical State**

Epoxy polymer mixture

Form

Paste

Color

Blue

Odor

Little or no odor

**Odor threshold**

Not determined

<b>Density (Specific gravity)</b>	9.5-9.7 lb/gal (1.1-1.2)
<b>Viscosity</b>	150,000 – 250,000 cps @ 25°C
<b>pH</b>	Data not available
<b>Melting point/freezing point</b>	Data not available
<b>Initial boiling point and boiling range</b>	Data not available
<b>Flash point</b>	>300°F, Pensky-Martens Closed Cup
<b>Evaporation rate</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Data not available
<b>Upper/lower flammability or explosive limits</b>	
Upper flammability limit (by volume)	N/A
Lower flammability limit (by volume)	N/A
<b>Material VOC</b>	None
<b>Vapor density</b>	Heavier than air
<b>Relative density</b>	Not determined
<b>Solubility</b>	Negligible, in water
<b>Partition coefficient: n-octanol/water</b>	3
<b>Auto-ignition temperature</b>	300°C (572.00°F)
<b>Decomposition temperature</b>	Not available

## 10. Stability And Reactivity

---

<b>Reactivity</b>	None
<b>Chemical stability</b>	Stable
<b>Possibility of hazardous reactions</b>	Hazardous polymerization will not occur
<b>Conditions to avoid</b>	Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke, resulting in hazardous decomposition products.
<b>Incompatible materials</b>	Strong oxidizing agents, Lewis and mineral acids.
<b>Hazardous decomposition products</b>	Oxides of carbon, aldehydes, acids.

## 11. Toxicological Information

---

### Information of likely routes of exposure

#### Diglycidyl Ether of Bisphenol A

Ingestion	LD50 Oral, Rat: 11,400 mg/kg LD50 Dermal, Rat: 2,200 mg/kg
Inhalation	Not available.
Skin contact	Skin – Erythema/Eschar 404 Acute Dermal Irritation/Corrosion, Rabbit: 1.5 – 2. Skin – Edema 404 Acute Dermal Irritation/Corrosion, Rabbit: 1.0 – 1.5. Skin – Moderate irritant, Rabbit: 24 hrs. Skin – Severe irritant, Rabbit: 24 hrs.



Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Reportable Quantity (RQ)
US DOT		Non-regulated		
TDG		Non-regulated		
IMO/IMDG	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (LIQUID EPOXY RESIN)	Class 9 III	
IATA (Cargo)	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (LIQUID EPOXY RESIN)	Class 9 III	
<b>Special precautions for user:</b>	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.			

## 15. Regulatory Information

---

### UNITED STATES

#### U.S. Federal Regulations

**United States – TSCA 12(b) – Chemical export notification:** None Required.  
**United States – TSCA 5(a)2 – Final significant new use rules:** Not Listed.  
**United States – TSCA 12(b) – Proposed significant new use rules:** None Required.  
**United States – TSCA 5(e) – Substance consent order:** Not listed.

#### California Prop. 65

This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

#### United States inventory (TSCA 8b)

All components are listed or exempted

### CANADA

#### WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

#### Canadian NPRI CEPA Toxic substances

None Required  
None Required

### INTERNATIONAL REGULATIONS

#### International Lists

**Australia inventory (AICS):** All components are listed or exempted.  
**Canada inventory:** All components are listed or exempted.  
**Japan inventory:** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.

## 16. Other Information, Including Date Of Preparation Or Last Revision

---

HMIS Rating                      WHMIS Rating: D2B

Health	2
Flammability	1
Physical Hazards	0

Date of printing                      03/14/22

Date of issue/Date of revision                      03/14/22

Date of previous issue                      None

Prepared By:                      EHS/Regulatory

**Abbreviations  
and Acronyms**

ACGIH: American Conference of Governmental Industrial Hygienists  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DOT: US Department of Transportation  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals  
HMIS: Hazardous Materials Identification System  
IARC: International Agency For Research on Cancer  
IATA: International Air Transport Association  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
IMDG: International Maritime Code for Dangerous Goods  
NFPA: National Fire Protection Association  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration  
SARA: Superfund Amendments and Reauthorization Act  
VOC: Volatile Organic Compound

The information contained herein is based on the data available to us and is believed to be correct. However, Kop Coat Inc./Kop Coat Marine makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Kop Coat Inc./Kop Coat Marine assumes no responsibility for injury from the use of the product described herein.