

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Safety Data Sheet dated 4/4/2023, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name : IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Trade code : 1650006

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product type and use: Painting product for car refinish and industrial job-professional use-

1.3. Details of the supplier of the safety data sheet

Supplier: Modern Recreational Technologies, Inc.
2220 Highway 70 SE., Suite 100 Hickory, NC 28602
800-728-8258

Competent person responsible for the safety data sheet:


1.4. Emergency telephone number:


Chemtrec: +1-800-424-9300 USA
Chemtrec: +1 703-527-3887 ex-USA
24 hrs./day, 7 days/week


SECTION 2: Hazards identification


2.1. Classification of the substance or mixture


EC regulation criteria 1272/2008 (CLP):

 Warning, Flam. Liq. 3, Flammable liquid and vapour.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, STOT SE 3, May cause respiratory irritation.

 Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

DECL10: This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE



Warning

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat - No smoking.

P261 Avoid breathing vapours.

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

xylene

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures













Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 12,5\%$ $< 15\%$	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-21194882 16-32	2.6/3 Flam. Liq. 3 H226 4.1/C3 Aquatic Chronic 3 H412 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332 3.2/2 Skin Irrit. 2 H315 3.3/2 Eye Irrit. 2 H319 3.8/3 STOT SE 3 H335 3.10/1 Asp. Tox. 1 H304

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

			 3.9/2 STOT RE 2 H373
>=10% -< 12,5%	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm]	Index number: 022-006-00-2 CAS: 13463-67-7 EC: 236-675-5	 3.6/2 Carc. 2 H351
>=10% -< 12,5%	n-butyl acetate	Index number: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH No.: 01-21194854 93-29	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H336
>=7% -< 10%	Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified	Index number: 649-356-00-4 CAS: 64742-95-6 EC: 265-199-0 REACH No.: 01-21194558 51-35	 2.6/3 Flam. Liq. 3 H226  3.8/3 STOT SE 3 H335  3.8/3 STOT SE 3 H336  3.10/1 Asp. Tox. 1 H304  4.1/C2 Aquatic Chronic 2 H411 DECLP (CLP)*
>=1% -< 3%	2-butoxyethyl acetate; butylglycol acetate	Index number: 607-038-00-2 CAS: 112-07-2 EC: 203-933-3 REACH No.: 01-21194751 12-47	 3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.1/4/Oral Acute Tox. 4 H302

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Eines No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store between 5 and 35°C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene - CAS: 1330-20-7

National - TWA: 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: pelle

EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

ACGIH - TWA(8h): 0.2 mg/m³ - Notes: Nanoscale particles; (R); A3 - LRT irr, pneumoconiosis

ACGIH - TWA(8h): 2.5 mg/m³ - Notes: Finescale particles; (R); A3 - LRT irr, pneumoconiosis

n-butyl acetate - CAS: 123-86-4

ACGIH - TWA(8h): 50 ppm - STEL: 150 ppm - Notes: Eye and URT irr

EU - TWA(8h): 241 mg/m³, 50 ppm - STEL: 723 mg/m³, 150 ppm

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

EU - TWA(8h): 133 mg/m³, 20 ppm - STEL: 333 mg/m³, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A3 - Hemolysis

DNEL Exposure Limit Values

xylene - CAS: 1330-20-7

Worker Professional: 3182 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 442 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 221 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 221 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects

n-butyl acetate - CAS: 123-86-4

Worker Professional: 960 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Worker Professional: 960 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Professional: 480 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Professional: 480 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, local effects

Worker Professional: 859.7 mg/kg - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Professional: 859.7 mg/kg - Exposure: Human Inhalation - Frequency: Short Term (acute)

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6

Worker Professional: 25 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 150 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 11 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 32 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

Worker Professional: 102 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Professional: 133 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

xylene - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/l

Target: Marine water - Value: 0.327 mg/l

Target: Marine water sediments - Value: 12.46 mg/l

Target: Freshwater sediments - Value: 12.46 mg/l

Target: 09 - Value: 6.58 mg/l

Target: Soil (agricultural) - Value: 2.31 mg/kg

Target: 08 - Value: 0.327 mg/l

n-butyl acetate - CAS: 123-86-4

Target: Fresh Water - Value: 0.18 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: 08 - Value: 0.36 mg/l

Target: 09 - Value: 35.6 mg/l

Target: Freshwater sediments - Value: 0.981 mg/kg

Target: Marine water sediments - Value: 0.0981 mg/kg

Target: Soil (agricultural) - Value: 0.0903 mg/kg

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

Target: Fresh Water - Value: 0.304 mg/l

Target: Marine water - Value: 0.0304 mg/l

Target: 08 - Value: 0.56 mg/l

Target: Freshwater sediments - Value: 2.03 mg/kg

Target: Marine water sediments - Value: 0.203 mg/kg

Target: Soil (agricultural) - Value: 0.68 mg/kg

Target: 09 - Value: 90 mg/l

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	N.A.	--	--
Odour:	CHARACTERISTIC	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	> 35 gradi C.	--	--
Flammability:	Flam. Liq. 3, H226	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	>= 23	--	--
Auto-ignition temperature:	400 gradi C.	--	--
Decomposition temperature:	N.A.	--	--
pH:		--	--
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)	--	--
Solubility in water:	Insolubile	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.D.	--	--
Density and/or relative density:	1.42 Kg/L	--	--
Relative vapour density:	>Air	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Properties	Value	Method:	Notes:
Explosive properties:	2/11 % Volume	--	--
Oxidizing properties:	N.D.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.)

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

xylylene - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat = 5000 Ppm - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 1700 mg/kg

n-butyl acetate - CAS: 123-86-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 10000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 21.1 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 14000 mg/kg

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 6193 mg/m³ - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 3160 mg/kg

Test: LD50 - Route: Oral - Species: Rat 3492 mg/kg

b) skin corrosion/irritation:

Test: Eye Irritant - Species: Rabbit 100 ul/kg

Test: Skin Irritant - Route: Skin - Species: Rabbit

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1880 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat > 3.91 mg/kg - Duration: 8h

Test: LD50 - Route: Skin - Species: Rabbit = 1500 mg/kg

xylylene - CAS: 1330-20-7

OBSERVATIONS ON HUMAN SUBJECTS NON-PROFESSIONAL EXPOSURED-
Effects following acute exposure:

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Symptoms of intense exposure are: dermatitis, eczema, irritation to the eyes and to the respiratory tract.

Inhaling the vapours can cause dizziness, headache, nausea, incoordination, excitability, narcosis, anaemia, and paraesthesia of the hands and feet.

PROFESSIONAL EXPOSURED- Effects following acute exposure:

Narcotic at high concentrations.

Irritation through inhalation at 200 ppm (TCLo). Inhalation of 200 ppm has irritating effects in human subjects.

Human subject (oral)(LDLo): 50 mg/kg.

Inhalatory human subject (LCLo) 10000 ppm/6h.

n-butyl acetate - CAS: 123-86-4

OBSERVATIONS ON HUMAN SUBJECTS:

Inhalation: 3300 ppm (16 mg/l), for short periods, cause serious irritation to the eyes and to the nose.

Inhalation: 200-300 ppm (1-1.4 mg/l), for short periods, cause moderate irritation to the eyes and to the nose.

Inhaling the vapours can irritate the respiratory system.

The vapours can cause headache and nausea. As a liquid it can irritate the eyes and cause conjunctivitis, it can irritate the skin and cause dermatitis and, if swallowed, causes inebriation, hallucinations and sedation.

Symptoms of illness at 500 ppm. Serious toxic effects at 2,000 ppm for 60 min.

TCLo: 200 ppm

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration \geq 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt sound working practices, so that the product is not released into the environment.

xylene - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae = 21 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 29 mg/l - Duration h: 96

Endpoint: EC50 - Species: Fish = 35 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia = 165 mg/l - Duration h: 24

n-butyl acetate - CAS: 123-86-4

e) Plant toxicity:

Endpoint: EC50 - Species: Algae = 675 mg/l - Duration h: 72

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified - CAS: 64742-95-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 3.2 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 9.2 mg/l - Duration h: 96

2-butoxyethyl acetate; butylglycol acetate - CAS: 112-07-2

e) Plant toxicity:

Endpoint: EC50 - Species: Algae = 1570 mg/l - Duration h: 72

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration \geq 0.1%

12.7. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 1263

IATA-UN Number: 1263

IMDG-UN Number: 1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

- 14.3. Transport hazard class(es)
- | | |
|-------------------------------------|----|
| ADR-Class: | 3 |
| ADR - Hazard identification number: | 30 |
| IATA-Class: | 3 |
| IMDG-Class: | 3 |
- 14.4. Packing group
- | | |
|---------------------|-----|
| ADR-Packing Group: | III |
| IATA-Packing group: | III |
| IMDG-Packing group: | III |
- 14.5. Environmental hazards
- | | |
|------------------------|-------------|
| IMDG-Marine pollutant: | NO |
| IMDG-EmS: | F-E,
S-E |
- 14.6. Special precautions for user
- | | |
|---|------------------|
| ADR-Subsidiary hazards: | - |
| ADR-S.P.: | 163 367 640E 650 |
| ADR-Transport category (Tunnel restriction code): | 3 (D/E) |
| IATA-Passenger Aircraft: | 355 |
| IATA-Subsidiary hazards: | - |
| IATA-Cargo Aircraft: | 366 |
| IATA-S.P.: | A3 A72 A192 |
| IATA-ERG: | 3L |
| IMDG-Subsidiary hazards: | - |
| IMDG-Stowage and handling: | Category A |
| IMDG-Segregation: | - |
- 14.7. Maritime transport in bulk according to IMO instruments
N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) n. 2020/878
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
 - Regulation (EU) n. 605/2014 (ATP 6 CLP)
 - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 - Regulation (EU) n. 2016/918 (ATP 8 CLP)
 - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 - Regulation (EU) n. 2017/776 (ATP 10 CLP)
 - Regulation (EU) n. 2018/669 (ATP 11 CLP)
 - Regulation (EU) n. 2018/1480 (ATP 13 CLP)
 - Regulation (EU) n. 2018/1480 (ATP 13 CLP)
 - Regulation (EU) n. 2019/521 (ATP 12 CLP)
 - Regulation (EU) n. 2020/217 (ATP 14 CLP)
 - Regulation (EU) n. 2020/1182 (ATP 15 CLP)
 - Regulation (EU) n. 2021/643 (ATP 16 CLP)
 - Regulation (EU) n. 2021/849 (ATP 17 CLP)

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 28

Restriction 29

Restriction 75

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H351 Suspected of causing cancer if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances (1983)

I.N.R.S. - Fiche Toxicologique

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.

Safety Data Sheet

REGULATORY REACH 1907/2006

1650006 IKONIKOLOR PRO 650 ACRYLIC URETHANE PRIMER GREY BASE

STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.